





LIGHTING FIXTURE MFG.

Sidemount Strip



GENERAL DESCRIPTION

An all purpose economy fluorescent 1-light sidemount strip that can be adapted to be a double sidemount, right angle or 3-light strip. All fixture parts snap together for ease of installation and maintenance.



SPECIFICATIONS

Housing: Die-formed heavy-gauge cold rolled steel. Fixture can be converted to double sidemount by removing socket tabs. Accepts slide-on or screw-on sockets. Side knockouts are included for a convenience outlet, a pull switch and conduit.

Cover: Snap-on type to simplify installation. Two covers are used for tandem units.

Ends and Socket Plates: Snap in for ease of assembly. Knockout tab for screw-on socket can be removed to make a right angle fixture.

Coupler: Used to join bodies together and as a center socket plate on tandem fixtures.

Finish: White polyester polymer with a minimum of 82% reflectivity.

Mounting: Designed for surface, chain and stem hanging. Can be installed as individual units or in continuous rows.

NOTES

Dimensions subject to change without notice.

Catalog No.	Lamps	Voltage	Length	Type
F-SM117	1 T8	120V-277V	24"	Bi-pin Shunted
F-SM125	1 T8	120V-277V	36"	Bi-pin Shunted
F-SM132	1 T8	120V-277V	48"	Bi-pin Shunted
F-SM217	2 T8	120V-277V	24"	Bi-pin Shunted
F-SM225	2 T8	120V-277V	36"	Bi-pin Shunted
F-SM232	2 T8	120V-277V	48"	Bi-pin Shunted